



POLARIMETER

Our user-friendly Polarimeters provide high accuracy and reliability in an easy to use instrument, suitable for manufacturing and laboratory applications.

Our Polarimeter is a compact system with convenient computer control that accurately measures Stokes Parameters 10 times per second. It quantifies the State of Polarization (SOP) and graphically displays the Poincaré Sphere, Polarization Ellipse, or running chart. The Meadowlark Optics system contains no spinning waveplates, motors, or other moving parts to wear or cause vibrations. Patented algorithms provide high accuracy and calibration versatility.



**Eigenstate Calibration Set sold separately.*



Key Features

- Compact
- No moving parts
- Broad wavelength range
- Fiber and free space versions
- Visible and near infrared versions

SPECIFICATIONS	
Absolute Degree of Polarization Accuracy	≤ 1%
Measurement Frequency	10 Hz
Resolution	0.001 of a Stokes Parameter
Maximum Operating Temperature	40 °C
Optical Head Dimensions	2.83 x 1.75 x 1.75 in.
Minimum Optical Power to maintain accuracy*	10 μW
Input Aperture	2 mm
These specifications describe performance at 23 ± 3 °C ambient temperature. *sensitivity can be increased to 1 μW by special request	
System Requirements: <ul style="list-style-type: none"> • Windows™ • USB Port • Use of LabView™ Instrument Library requires LabView™ version 6.1 or newer full development system. 	

ORDERING INFORMATION		
Wavelength Range	Version	Part Number
450-1100 (nm)	Visible	PMI - VIS
900-1700 (nm)	Near Infrared	PMI - NIR

OPTIONAL ACCESSORIES
Eigenstate Generator Set* Fiber optic cable adapter - Visible - Infrared Angle-polished fiber collimator adapter Calibration at additional wavelengths *The Eigenstate Generator Set enables precise Polarimeter recalibration

